

- 2. OBJECTS SHOWN IN HEAVY LINE WEIGHT ARE NEW.
- 3. PATCH AND REPAIR ANY DAMAGED WALLS AND FLOORS DURING RENOVATION AND CONSTRUCTION TO MATCH EXISTING CONDITIONS.

FLAG NOTES:

- 1 EXISTING FLOORING AND EXISTING FLOOR DECK. FIELD VERIFY EXISTING 1ST FLOOR DECK DEPTH. TOP OF FLOOR ELEVATION FOR THE NEW FIRST FLOOR DECK SHALL BE LOCATED AT THE SAME ELEVATION AS THE TOP OF FLOOR ELEVATION FOR THE EXISTING FLOOR DECK. SEE NOTE #2 AND DRAWING SO2.
- (2) NEW LAYERS 3/4" T&G PLYWOOD DECKING ON NEW FLOOR DECK. FIELD VERIFY EXISTING 1ST FLOOR DECK DEPTH. TOP OF FLOOR ELEVATION FOR THE NEW FIRST FLOOR DECK SHALL BE LOCATED AT THE SAME ELEVATION AS THE TOP OF FLOOR ELEVATION FOR THE EXISTING FLOOR DECK. SEE DRAWING S02.
- 3 EXISTING/NEW WALL SYSTEM. SEE WALL SECTION A ON DRAWING A7. REMOVE EXISTING VINYL SIDING AND FIELD VERIFY CONDITIONS. INSTALL (1) LAYER TYVEK 1/2" CDX PLYWOOD, 1/2" INSULATED PANEL AND TYVEK MOISTURE BARRIER IF REQUIRED FOR INSTALLATION OF NEW BRICK VENEER WALL SYSTEM.
- 4 NEW WALL SYSTEM. SEE WALL SECTION A ON DRAWING A7.
- 5 NEW WALL SYSTEM. SEE WALL SECTION B ON DRAWING A7.
- (6) (2) 2x16 MAIN ROOF STRUCTURAL SUPPORT BEAM. GLUE AND BOLT BEAMS TOGETHER. STAGGER BOLTS AT TOP AND BOTTOM OF BEAMS AT 16" O.C.
- $\overline{7}$ 2x10 RIDGE BEAM.
- $\langle 8 \rangle$ 2x6 PLATE.
- 9 2x6 RAFTERS AT 16" O.C.
- $\langle 10 \rangle$ 2x8 RAFTERS AT 16" O.C.
- $\langle 11 \rangle$ 2x10 RAFTER AT 16" O.C.
- $\langle 12 \rangle$ 1/2" DRYWALL.
- (13) 5 1/4"x8" BEAM SUPPORT COLUMN.
- 14 1"x3" CROSS BRACING FOR FLOOR JOISTS. LOCATE ROWS OF CROSS BRACING AT 8'-0" O.C. MAX. AND INSTALL PER JOIST MANUFACTURER'S RECOMMENDATIONS.
- ROOF RAFTERS SHOWN IN HIDDEN LIGHT TYPE ARE SHOWN FOR REFERENCE ONLY.
- (16) ROOF RAFTERS FOR REAR GABLE.

REV: REVISION DESCRIPTION:



ANDY'S BEST CAD 9715 S. MERIMBULA ST. LITTLETON, CO 80130 303-791-1622 WWW ANDYSHESTCAD COM

10/11/02

DRAWN: DESIGNED: CLIENT: DATE: SCALE:

DRAWING TITLE:
RESIDENTIAL
HOME PLANS
ARCH. SECTION A—A

DRAWING NO.:

A5 05 0F 07

DO NOT SCALE DRAWINGS
ALL DIMENSIONS IN INCHES

UNLESS NOTED OTHERWISE