

GENERAL NOTES:

1. OBJECTS SHOWN IN LIGHT LINE WEIGHT ARE EXISTING TO REMAIN.

- 2. OBJECTS SHOWN IN HEAVY LINE WEIGHT ARE NEW.
- 3. PATCH AND REPAIR ANY DAMAGED WALLS AND FLOORS DURING RENOVATION AND CONSTRUCTION TO MATCH EXISTING CONDITIONS.

FLAG NOTES:

- $\langle 1 \rangle$ SEE WALL SECTION C ON DRAWING A7.
- 2 SEE WALL SECTION D ON DRAWING A7.
- (2) 2x16 MAIN ROOF STRUCTURAL SUPPORT BEAM. GLUE AND BOLT BEAMS TOGETHER. STAGGER BOLTS AT TOP AND BOTTOM OF BEAM AT 16" O.C.
- $\langle 4 \rangle$ 2x10 RIDGE BEAM.
- $\langle 5 \rangle$ 2x6 PLATE TOP & BOTTOM OF RIDGE BEAM.
- $\langle 6 \rangle$ 2x10 JOISTS AT 16" O.C. FOR VAULTED ROOF.
- $\langle 7 \rangle$ 2x8 ROOF JOISTS AT 16" O.C.

- $\langle 8 \rangle$ 2x10 JOISTS WHERE INDICATED.
- $\langle 9 \rangle$ 1/2" DRYWALL.
- (10) 5 1/4"x8" BEAM SUPPORT COLUMN.
- 1"x3" CROSS BRACING FOR FLOOR JOISTS. LOCATE ROWS OF CROSS BRACING AT 8'-0" O.C. MAX. AND INSTALL PER FLOOR JOIST MANUFACTURER'S RECOMMENDATIONS.
- (12) TOP PLATES OF EXTERIOR WALL.
- (13) 2x6 JOISTS AT 16" O.C. FOR VAULTED CEILING.

DO NOT SCALE DRAWINGS

ALL DIMENSIONS IN INCHES UNLESS NOTED OTHERWISE

F CAD RIMBULA ST. 50 80130 622

> 971 III 10/11/02 30:

DRAWN: A
DESIGNED:
CLIENT:
DATE:

DRAWING TITLE:
RESIDENTIAL
HOME PLANS

DRAWING NO.:

A6 06 0F 07